

DELTA PLUS · HEAD PROTECTION

SUPER QUARTZ

Product code: SUPE0P101 · Series: SUPER QUARTZ



Delta Plus SUPER QUARTZ: ABS-polycarbonate shell, non-vented, slip ratchet, 8-point polymer harness, 4-point jugular; EN 397 (MM LD; -30 °C to +150 °C; 440 Vac) and EN 50365 Class 0 declared.

- 01 EN 397 (MM, LD, 440 Vac; -30 °C to +150 °C)
- 02 EN 50365 Class 0
- 03 ABS-polycarbonate shell
- 04 Non-vented
- 05 Slip ratchet

Technical data

BRAND	Delta Plus
MODEL	SUPER QUARTZ
EN 397 OPTIONAL	-30 °C · +150 °C · MM (molten metal) · LD (lateral deformation) · 440 Vac
ELECTRICAL INSULATION	EN 50365 Class 0 (1000 V)
VENTILATION	Non-ventilated
HARNESS POINTS	8
ADJUSTMENT	Sliding strap
CHIN STRAP	4-point
HEAD SIZE	53–63 cm
SHELL MATERIAL	ABS - Polycarbonate
WEIGHT	410 g
COLOURS	White
SERVICE LIFE	84 months from manufacturing; 60 months from first use

Standards

STANDARD	EDITION	PERFORMANCE
EN 397	2012	MM LD -30°C +150°C 440VAC
EN 50365	—	Class 0

Variants

CODE	FEATURE
SUPE0P101	White

Areas of use

Construction · General industry · Chemical · Petrochemical / refinery · Energy · Logistics / warehousing